

800.364.7681



www.DOGIPARK.com

The **Smart** Dog Park Solution.
A DOGIPOT® Brand.

 **PLAYGROUNDS FOR DOGS™**

FIRE HYDRANT (ITEM #7731) SPECIFICATION AND INSTALLATION SHEET



YOUR PLAYGROUNDS FOR DOGS DECORATIVE FIRE HYDRANT INCLUDES:

- 1 Red decorative fire hydrant
- 4 Red powder coated in-ground mounting J-rods

PLEASE CHECK THE ABOVE INVENTORY AND CALL YOUR DISTRIBUTOR IF ANY PARTS ARE MISSING.

INSTALLATION AND OPERATION INSTRUCTIONS

- 1 Find the desired location that is flat and accessible on all sides for dogs to enjoy the Decorative DOGIPARK® Fire Hydrant. It is recommended to remove any sod around the Fire Hydrant so that it can be installed on a flat area and surrounded by mulch.
2. Mark the location of the (4) four holes on the ground where the ground mount installation j-rods will be inserted into the ground through the base of the fire hydrant.
3. Use a broom stick, tomato, ground stake or similar items to pound into the ground to create 4 holes approximately 2-3" wide and 14" deep for the j-rods to be inserted.
4. Lay the fire hydrant on the ground sideways and slide each j-rod into each hole on the base of the fire hydrant to prepare to install into the ground.
- 5 Per the directions on the bag, pour some quick setting concrete into each hole filling them up.
6. Position the fire hydrant in the installation area and slide the installed j-rods into each concrete-filled hole.
7. The j-rods may need to be swiveled back and forth gently to get them to slide all the way down into the wet concrete filled holes. If necessary, gently hammer the j-rods, into their holes. **CAUTION:** The powder coating on the top of the j-rods can be chipped and damaged if the top of the j-rods are not covered with a soft item if hammered. Proceed slowly and tap gently to ensure they are not damaged. The fire hydrant will need to set and cure per the directions on the quick setting concrete that was used.
8. It is recommended to surround the fire hydrant with a wood mulch to create a buffer so the landscapers maintaining the area do not hit the fire hydrant with a lawnmower or weed trimmer and so that there is no grass immediately around it that will be destroyed by the dog urine that likely will increase in the area due to the presence of the fire hydrant.
9. The Decorative DOGIPARK® Fire Hydrant may also be surface mounted instead of ground mounting. Surface mounting hardware has NOT be included and the j-rods will not be necessary for this type of installation. **CAUTION: DO NOT OVERTIGHTEN** any surface mounting hardware. This may damage the base of the fire hydrant.

WARNING: THIS IS A DECORATIVE FIRE HYDRANT TO ADD CHARACTER TO YOUR DOG PARK AND FOR DOGS TO ENJOY. IT IS NOT DESIGNED FOR PEOPLE TO CLIMB OR STAND ON. THIS COULD DAMAGE THE FIRE HYDRANT AND INCREASE THE CHANCE OF INJURY. DO NOT CLIMB, SIT, LEAN OR STAND ON THE FIRE HYDRANT AT ANY TIME.

PLAYGROUNDS FOR DOGS™

FIRE HYDRANT (ITEM #7731)

SPECIFICATION AND INSTALLATION SHEET



PRODUCT DETAILS:

- Made of unsaturated Poly Resin - so it is light and durable
- Coated with Red Poly Urethane Paint to seal out urine, dirt and other natural surface enemies.
- 5 year warranty on coating
- Total Weight 29 lbs.

SAFETY WARNINGS AND EQUIPMENT MAINTENANCE RECOMMENDATIONS

- **PLEASE READ THESE IMPORTANT SAFETY WARNINGS AND KEEP ON FILE FOR FUTURE REFERENCE REGARDING INSPECTION REMINDERS AND LIST OF PARTS.**
- Follow installation instructions and find a safe, suitable location for equipment use.
- All products should be in-ground or surface mounted and securely fastened to concrete. Concrete footers should never protrude above the ground where they are exposed and could create a safety hazard. Ground covering, such as mulch, is recommended over the buried footers and under an around the equipment.
- Regular scheduled review of equipment should be conducted to ensure there is no existing damage caused by wear and tear, improper use or vandalism.
- All equipment should be free from rust or other structural damage. Replace or repair in the event any rust exists that could affect the structural integrity of the equipment.
- Any areas where the coating has been removed should be repainted to deter rusting or other damage.
- Any protruding bolts, rough or sharp edges should be covered, capped or removed. Inspect for broken, bent or worn pieces and replace if present.
- Never add components not intended for this equipment. **EQUIPMENT IS NOT INTENDED FOR USE BY PEOPLE. THE EQUIPMENT IS SOLELY INTENDED AND DESIGNED FOR DOG USE ONLY.**
- Proper and regular maintenance of equipment includes, but is not limited to, inspection of footings, all bolts and connection points, edges, landing areas, coatings and surfaces. This includes regular tightening of bolts, nuts and screws.
- ANY WORN OR BROKEN PARTS, BOLTS, NUTS, SCREWS, INSTABILITY IN THE FOOTERS AND THE LIKE SHOULD BE REPLACED IMMEDIATELY TO PREVENT ANY INJURY.

WARRANTY

DOGIPOT® warrants to the original consumer purchaser that our **DOGIPARK®** brand products will be free from defects in material workmanship under normal use for a period of two (2) years from the date of purchase when installed and maintained properly.

DOGIPOT® may elect to repair or replace any defective **DOGIPARK®** product covered by our warranty. Our warranty does not cover defects caused by misuse, abuse, vandalism, negligence, alterations, environmental conditions, extreme weather conditions, manmade or natural disasters, lack of maintenance, improper installation, storage or handling or normal wear and tear from use.

DOGIPOT® provides a limited warranty for the **RUFFCOAT™** and Thermoplastic coated elements for 5 years.

Damages or loss in transit is the responsibility of the carrier, whether visible or concealed. It is the responsibility of the recipient to ensure that the order is received both complete and without damages. Before signing receipt, inspect the shipment immediately and completely. Note any damages or shortages on the bill of lading. Damage reports must be filed within ten (10) days. **DOGIPOT®** is not responsible for lost damages or loss in transit. Title to all goods passes to the customer at the time of shipment. **DOGIPOT®** will assist in filing claims if the freight arrangement was made by **DOGIPOT®** at your request. Cancellations and returns are only accepted with the approval of **DOGIPOT®**. No equipment shall be returned without a Return Materials Authorization which is issued by customer service. Any returned equipment must be returned in the original packaging and wrapped and stuffed to avoid damage, or in a similar suitable condition. A restocking charge of up to 25% will be applied to all returned goods when the error is not that of **DOGIPOT®**. The customer is responsible for all freight charges to return any equipment.