

UT Series 10 and 12 Foot Side Access Rectangular Table with Lumber Top and Seats

SPECIFICATION
BULLETIN
#SPC-TB-117

REV. 09-17



Model UT/G-12UP/SA 12 Ft. Wheelchair Accessible Heavy Duty Portable Rectangular Table with Hot Dip Galvanized Frames and Untreated Pine top and seats. Table provides side access for two wheelchairs.

- · ADA compliant access for two wheelchair
- · Nontip, nontrip, walk-through design
- All welded end frames are fabricated from 1.66" diameter steel pipe
- Die-formed center channel and diagonal braces align and strengthen entire table
- Frames are hot dip galvanized after fabrication for superior corrosion resistance
- Precision drilled, Untreated #1 Southern Yellow Pine Top and seat Planks
- Limited lifetime warranty on frames

SPECIFICATIONS:

- **UT Series** end frames are one-piece welded construction, fabricated from 1.660" O.D. (1-5/8" O.D.) steel pipe to meet 1-1/4" nominal pipe size specifications with 2" x 2" x 1/8" die formed steel angle for attaching the seats and top.
- Table frame design incorporates nontip, nontrip, walk-through design features.
- Table provides two wheelchair spaces created by attaching one short seat and one long seat to end frames diagonally opposite each other. Short seats are supported by a 11 ga. steel plate bracket. Gap between seats create a ADA recommended space of 30" wide, 19" deep, and 27" from ground to bottom of table top for knee space, and minimum 9" above ground extending a total of 24" deep for toe space. Indicated by "/SA" at end of model no., e.g. UT/G-10UP/SA.
- Nominal table height, 30". Nominal seat height, 18".
- Model UT/G-10UP/SA is a nominal 10 ft. long with three frames, one 21-3/4" long seat and one 67-3/4" long seat on each side.
- Model UT/G-12UP/SA is a nominal 12 ft. long with three frames, one 21-3/4" long seat and one 82-5/8" long seat on each side.
- Frames are supported by diagonal braces of 1-5/16" O.D. x 14 ga. wall steel pipe that connect to a die-formed steel channel designed to align and provide attachment to the table top.
- **Standard:** All steel frame components are hot-dip galvanized after fabrication to ASTM-A123 to maintain an average zinc coating of 2.0 oz. per sq. ft. of surface area (indicated by "/G" in model no., e.g. UT/G-10UP/SA).
- All fasteners are provided for assembly.
- •Standard: Lumber is Untreated #1 grade Southern Yellow Pine (indicated by "UP" in model no., e.g. UT/G-10UP/SA) 2" x 10" nominal sized planks, kiln dried to reduce moisture content. All lumber is precision drilled to facilitate assembly and has all exposed edges removed to a 3/8" radius.
- **Optional:** All steel frame components have powder coat finish. See Specification Bulletin #SPC-CO-001.
- **Optional:** Treated #1 Southern Yellow Pine is readily available and is pressure treated (KDAT) to preserve wood against decay. To specify, change "UP" in model no. to "TP", e.g. UT/G-10TP/SA. (Cedar, Fir and Redwood are available when in stock —please inquire.)

AVAILABLE OPTIONS

10' or 12' length

Powder Coat Finish in choice of colors for steel frame components

Pressure treated #1 Southern Yellow Pine lumber (Cedar, Fir, or Redwood lumber when in stock)

