

WXT Series 10 and 12 Foot Universal Access Table with Aluminum Top and Seats

SPECIFICATION
BULLETIN
#SPC-TB-174

REV. 09-17



Model WXT/CU-10AL 10 Ft. Portable, Universal Access Rectangular Table with Blue powder Coated Frames and Clear Anodized Aluminum top and seats

- Constructed specifically for heavy use areas
- Nontip, nontrip, walk-through design with wheelchair access at each end
- Full capacity seating when wheelchairs are not in place
- All-welded end frames are fabricated from 2-3/8" diameter steel pipe
- Die-formed center channel and diagonal braces align and strengthen entire table
- Frames are hot-dip galvanized after fabrication for superior corrosion resistance
- Structurally reinforced extruded Aluminum Top and Seats with clear anodized finish
- Limited Lifetime Warranty on frames

AVAILABLE OPTIONS

10' or 12' lengths

Powder Coat Finish in choice of colors on steel frame components

Powder Coat Finish in choice of colors on Aluminum top and seats

SPECIFICATIONS:

- WXT Series end frames are one-piece welded construction, fabricated from 2.375" (2-3/8") O.D. x 10 ga. wall steel pipe to meet 2" nominal steel pipe size specifications with 2" x 2" x 1/8" die-formed steel angle for attaching the seats and top. Bends are tightly formed to prevent tipping when weight is on one side.
- The frame design provides the ADA recommended wheelchair clearances under the table top of: 30" wide, 27" high and 24" total knee and toe clearance (19" knee + 5" toe) at each end of the table while maintaining the full seating capacity of the table for common use.
- Table frame design incorporates nontip, nontrip, walk-through design features.
- Model WXT/G-10 has a nom. 10 ft. in length with three frames.
- Model WXT/G-12 has a nom. 12 ft. in length with three frames.
- Nominal table height is 30". Frame design provides a nominal 28" of clearance from ground level to the underside of table. Nominal seat height is 18".
- Frames are supported by diagonal braces of 1-5/16" O.D. x 14 ga. wall steel pipe that connect to a die-formed steel channel designed to align and provide attachment to the table top.
- All fasteners are provided for assembly.
- **Standard:** All steel frame components are hot-dip galvanized after fabrication to ASTM-A123 to maintain an average zinc coating of 2.0 oz. per sq. ft. of surface area (indicated by "/G" in model no., e.g. WXT/G-10AL).
- Aluminum is extruded 6063-T6 aluminum alloy in planks with dimensions equivalent to that of 2" x 10" nominal sized lumber. The plank design is 1-3/4" x 9-5/8" with four structural reinforcement ribs for greater rigidity. Aluminum planks are provided with a clear anodized finish as per anodizing specification 204 R1. Aluminum clips to fasten planks to frames are included.
- Channel end caps are of extruded 6063-T6 aluminum alloy provided with a clear anodized finish as per anodizing specification 204 R1. End caps are press fitted over ends of aluminum planks and mechanically fastened in place at the factory.
- Table top is assembled into single unit at the factory with one-piece end caps across each end.
- **Optional:** All steel frame components have powder coat finish. See Specification Bulletin #SPC-CO-001.
- **Optional:** Aluminum top and seats have powder coat finish. See Specification Bulletin #SPC-CO-001.
- •U.S. Patent Nos. D489,539; D490,992; D493,291; D496,799; D497,262; 6,918,630

