## Pilot Roc

SITE PRODUCTS

## XT Series 6 Foot Wheelchair Accessible Table Extended One End with V-Type Thermo-plastic #SPC-TB-057 **Coated Expanded Steel Top and Seats**

**SPECIFICATION** BULLETIN

REV. 02-25



Model XT/CB-6VA/E 6 Ft. Wheelchair Accessible Table with black powder coat frames and gray V-Type thermo-plastic coated expanded steel top and seats

- Snow load/extreme load rated to 948 lbs. per square foot
- Top and seats designed for more abusive environments such as high elevations where snow loads can destroy average tables
- Extended top for wheelchair accessibility at one end
- Nontip, nontrip, walk-through design
- · All welded end frames are fabricated from 2-3/8" diameter steel pipe
- · Die-formed channels and diagonal braces support table extensions
- Frames are hot-dip galvanized after fabrication for superior corrosion resistance
- Thermo-plastic Coating heat fused to Expanded Steel Top and Seats for durability
- Thermo-plastic Coating formulated with U.V. stabilizers for ultraviolet protection
- Limited lifetime warranty on frames

## **AVAILABLE OPTIONS**

Powder Coat Finish in choice of colors for steel frame components

Choice of colors of Thermo-plastic Coating

## **SPECIFICATIONS:**

- •XT Series end frames are one-piece welded construction, fabricated from 2.375" (2-3/8" O.D.) steel pipe to meet 2" nominal steel pipe size specifications with 2" x 2" x 1/8" die formed steel angle for attaching the seats and tops. "Outriggers" are attached to the frame on the extended end of the table for added stability.
- Snow Load Capacity: This table has been independently tested to meet the U.S. Forest Service snow load requirement of 948 lbs. per square foot. (Test results available upon request)
- Table top extends 2 ft. beyond seats (indicated by "/E" in model no., e.g. XT/G-6VW/E) to provide the ADA recommended wheelchair clearances of: 30" wide, 27" under table (ground to bottom of table top), and 24" total knee and toe clearance (19" + 5").
- A diagonal brace of 1-5/16" O.D. steel pipe and a die-formed steel channel is provided to support extended portions of table
- Model XT/G-6VW/E has a nom. 8 ft. long top and 6 ft. long seats. Includes frame stabilizing outriggers.
- Frames are supported by diagonal braces of 1-5/16" O.D. steel pipe that connect to the table top.
- Table height provides a nominal 28" of clearance from ground level to the underside of the table top. Nominal seat height is 18-1/2".
- **Standard:** All steel frame components are hot-dip galvanized after fabrication to ASTM-A123 to maintain an average zinc coating of 2.0 oz. per sq. ft. of surface area (indicated by "/G" in model no., e.g. XT/G-6VW/E).
- All fasteners are provided for assembly.
- V-Type table top and seats are each a one-piece welded construction, fabricated from a 3/4-#9 expanded steel surface with 10 ga. x 2-1/2" roll-formed vertical edges on all sides and reinforced by a 10 ga. die-formed angle substructure. Substructure includes all mounting holes for easy assembly of
- **Standard:** All steel surfaces of the top and seats are covered with a thermo-plastic coating in a Brown color (indicated by "VW" in model no., e.g. XT/G-6VW/E). The UV-stabilized thermo-plastic coating is applied in a multi step process of material preparation and finish application designed to permanently heat fuse and bond the finish to the steel. The thermo-plastic polyethylene finish is impact resistant, does not support mold or mildew, and the textured matte surface is less susceptible to marring and scuffing.
- Optional: Color choices of powder coated steel frame components. See Specification Bulletin #SPC-CO-001.
- Optional: Color choices of Thermo-plastic coated steel components. For optional colors choices see Specification Bulletin #SPC-CO-001.

RJ Thomas Mfg. Co., Inc.

