

## APT Series 6 Foot Multi Pedestal Wheelchair Accessible Table Extended One Foot Both Ends with Lumber Top and Seats

SPECIFICATION
BULLETIN
#SPC-TB-265

REV. 11-19



Model APT/G-6UP/E1 6 ft. Wheelchair Accessible Multi Pedestal Embedded Mount Table, extended 1 ft. each end, with Hot dip Galvanized Frames and Untreated Southern Yellow Pine Planks

- ADA compliant wheelchair accessibility at both ends
- Permanent embedded mounting
- Nontrip, walk-through design
- Sturdy 3" x 6" rectangular steel tube pedestals
- Frames are hot-dip galvanized after fabrication for superior corrosion resistance
- Precision drilled, Untreated #1 Southern Yellow Pine Seat and Top Planks
- Quality construction throughout

## **SPECIFICATIONS:**

- •APT Series table top and seat end frames are one-piece welded construction, fabricated from 3" x 6" x 1/8" wall rectangular structural steel tubing with 2" x 2" x 3/16" A-36 structural grade steel angle for attaching the seats and tops. Exposed ends of rectangular tubing are permanently sealed with welded-on steel end caps. Frames are designed to be embedded in a concrete footing.
- Table top extends 1 ft. beyond seats (indicated by "/E1" in model no., e.g. APT/G-6UP/E1) to provide the ADA recommended wheelchair clearances of: 30" wide, 27" under table (ground to bottom of table top), and 24" total knee and toe clearance (19" + 5").
- Model APT/G-6UP/E1 has a nominal 8 ft. long top and 6 ft. long seats.
- Nominal table height is 32". Nominal seat height is 18-1/2".
- All fasteners are provided for assembly.
- **Standard:** All frame components are hot-dip galvanized after fabrication to ASTM-A123 to maintain an average zinc coating of 2.0 oz. per sq. ft. of surface area (indicated by "/**G**" in model no., e.g. APT/**G**-6UP/E1).
- •Standard: Lumber shall be Untreated #1 grade Southern Yellow Pine (indicated by "UP" in model no., e.g. APT/G-6UP/E1) 2" x 10" nominal sized planks, kiln dried to reduce moisture content. All lumber is precision drilled to facilitate assembly and has all exposed edges removed to a 3/8" radius.
- **Optional:** Color choices of powder coated steel frame components. For optional colors choices see Specification Bulletin #SPC-CO-001.
- **Optional:** Treated #1 Southern Yellow Pine is readily available and is pressure treated (KDAT) to preserve wood against decay. To specify, change "UP" in model no. to "TP", e.g. APT/G-6TP/E1. (Cedar, Fir and Redwood are available when in stock —please inquire.)
- **Optional:** Frames are provided with a 3/8" x 8" x 8" steel base plate to bolt table to existing concrete pad. To specify add "/P" after the "APT" in the model no., e.g. APT/P/G-6UP/E1. (Anchor bolts not included.)

## **AVAILABLE OPTIONS**

Choice of colors of Powder Coat Finish for steel frame components

Pressure treated #1 Southern Yellow Pine lumber (Cedar, Fir, or Redwood lumber when in stock) Surface mount base plate

