

PQT3-4 Series Wheelchair Accessible 4 Foot Square Pedestal Table with Lumber Top and Seats

SPECIFICATION
BULLETIN
#SPC-TB-273

REV. 03-23



Model PQT3/G-4UP 48" Square Top, Wheelchair Accessible, Embedded Mount Table with Galvanized Frame and Untreated Yellow Pine Top and Seats.

- Three seats and one open side for wheelchair access
- Square design optimizes table top usage and creates a more intimate setting
- Square table fits into more compact areas
- Permanent embedded mounting
- Sturdy 6" square center pedestal, 3-1/2" diameter round radial seat supports
- Precision drilled, Untreated #1 Southern Yellow Pine Seat and Top Planks
- Quality construction throughout

AVAILABLE OPTIONS

Powder Coat Finish in choice of colors for steel frame components

Pressure treated #1 Southern Yellow Pine lumber (Cedar, Fir, or Redwood lumber when in stock)
Umbrellas

Surface mount base plate

SPECIFICATIONS:

- Model PQT3-4 table frame incorporates a 6" square single pedestal post designed to embed into a concrete footing.
- \bullet Three seat support frames are each a one-piece welded construction of 3-1/2" dia. x 11 ga. wall structural steel tubing, a 2-3/8" dia. 10 ga. wall tube, and 2" x 2" x 1/8" die formed steel angles designed to resist lateral torsion and deflection when loaded.
- Model PQT3-4 tables have been adapted for wheelchair accessibility. By removing one or more arm/seat structures the side of the table is opened to provide wheelchair access.
- Frame is designed in a theft-proof manner with all fasteners extending into the post to prevent removal after assembly.
- **Model PQT3-4** has a nominal 48" square table top utilizing (5) top planks.
- \bullet Nominal table height is 31-13/16". Nominal seat height shall be 19-7/8".
- \bullet Top planks are supported by a subframe of 2" x 2" x 1/8" die formed steel angle, 10 ga. steel channel, and 2-3/8" round tubing.
- All galvanized fasteners are provided for table assembly.
- **Standard:** All frame components are hot-dip galvanized after fabrication to ASTM-A123 to maintain an average zinc coating of 2.0 oz. per sq. ft. of surface area (indicated by "/**G**" in model no., e.g. PQT3/**G**-4UP).
- Standard: Lumber is Untreated #1 grade Southern Yellow Pine (indicated by "UP" in model no., e.g. PQT3/G-4UP) 2" x 10" nominal sized planks, kiln dried to reduce moisture content. All lumber is precision drilled to facilitate assembly and has all exposed edges removed to a 3/8" radius.
- **Optional:** Treated #1 Southern Yellow Pine is readily available and is pressure treated (KDAT) to preserve wood against decay. To specify, change "UP" in model no. to "**TP**", e.g. PQT3/G-4**TP**. (Cedar, Fir and Redwood are available when in stock –please inquire.)
- **Optional:** Color choices of powder coated steel frame components. For optional colors choices see Specification Bulletin #SPC-CO-001.
- Optional: Tables is provided with umbrella holes in table tops and cup and collar sets for mounting umbrellas. To specify, add " $/\mathbf{U}$ " to the end of the model no., e.g. PQT3/G-4UP/ \mathbf{U} .
- **Optional:** Frame is provided with a 3/8" x 15-3/4" x 15-3/4" steel base plate to bolt table to existing concrete pad. To specify add "/**P**" after the PQT in the model no., e.g. PQT3/**P**/G-4UP. (Anchor bolts not included.)

