

WPTS Series 6 and 8 foot Universal Access Portable Table with Thermo-plastic Coated Steel Channel Top and Seats

SPECIFICATION BULLETIN
#SPC-TB-245

REV. 02-21



Model WPTS/G-6SC/TT Universal accessible portable rectangular table, 6 ft. long with hot dip galvanized frames and tan thermo-plastic coated steel channel top and seats.

- Nontip, nontrip, walk-through design, wheelchair accessibility at each end
- Full capacity seating when wheelchairs are not in place
- All welded end frames are fabricated from 3" x 6" rectangular and 2-1/2" square steel tubing
- Diagonal braces align and strengthen entire table
- Frames are hot dip galvanized after fabrication for superior corrosion resistance
- Thermo-plastic Coating heat fused to Steel Channel Top and Seats for durability
- Thermo-plastic coating formulated with U.V. stabilizers for ultraviolet protection

AVAILABLE OPTIONS

6' or 8' lengths

Powder Coat Finish in choice of colors on steel frame components

Choice of colors of thermo-plastic coating

SPECIFICATIONS:

- WPTS Series end frames are one-piece welded construction, fabricated from $3" \times 6" \times 1/8"$ wall rectangular steel tube top and seat supports connected by $2-1/2" \times 1/8"$ wall square tube with $2" \times 2" \times 3/16"$ die-formed steel angle for attaching seats and tops.
- Model WPTS frame design provides the ADA recommended wheelchair clearances under the table top of: 30" wide, 27" high and 24" total knee and toe clearance (19" knee + 5" toe) at each end of the table while maintaining full seating capacity of the table.
- Frame design incorporates nontip, nontrip, walk-through features.
- **Model WPTS/G-6** is nom. 6 ft. long, wheelchair accessible both ends with ADA compliant knee/toe clearance.
- **Model WPTS/G-8** is nom. 8 ft. long, wheelchair accessible both ends with ADA compliant knee/toe clearance.
- Nominal table height is 31-1/2". Frame design provides a nominal 28" of clearance from ground level to the underside of table. Nominal seat height is 18".
- Frames are supported by diagonal braces of 1-5/16" O.D. x 14 ga. wall steel pipe connected to the table top.
- All fasteners are provided for assembly.
- **Standard:** All steel frame components are hot-dip galvanized after fabrication to ASTM-A123 to maintain an average zinc coating of 2.0 oz. per sq. ft. of surface area (indicated by "/G" in model no., e.g. WPTS/**G**-6SC/TW).
- Steel channel top and seats are each a one-piece welded construction, fabricated from 16 ga. steel plate formed to nominal dimensions of 2" x 4" lumber, with 10 ga. bracing (indicated by "SC" in model no., e.g. WPTS/G-6**SC**/TW). Structure includes all mounting holes for assembly of table.
- Standard: All steel surfaces of the top and seats are covered with a thermo-plastic coating in a Brown color (indicated by "/TW" in model no., e.g. WPTS/G-6SC/TW). The UV-stabilized thermo-plastic coating is applied in a multi step process of material preparation and finish application designed to permanently heat fuse and bond the finish to the steel. The thermo-plastic polyethylene finish is impact resistant, does not support mold or mildew, and the textured matte surface is less susceptible to marring and scuffing.
- **Optional:** All steel frame components have powder coat finish. See Specification Bulletin #SPC-CO-001.
- **Optional:** Color choices of Thermo-plastic coated steel components. See Specification Bulletin #SPC-CO-001.
- •U.S. Patent Nos. D489,539; D490,992; D493,291; D496,799; D497,262; 6,918,630

